

## UC400 Cat6 patch

Copper flexible patch cables 26 & 27AWG



### Technical Data

#### Application-Installation

Work area and patch cord cable  
IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T;  
IEEE 802.5 16 MB;  
ISDN; TPDDI; ATM

#### Construction

##### 1. Conductor

- U/UTP:** Stranded Cu-wire, tinned Ø 0.51 mm (AWG26)
- U/FTP:** stranded bare copper wire Ø 0.42 mm (AWG27)

##### 2. Insulation

- U/UTP:** Polyethylene
- U/FTP:** Foam Skin Polyethylene

##### 3. Twisting

-2 cores to the pair

##### 4. Screen

- U/UTP:** -
- U/FTP:** STP: Al-laminated plastic foil, patented wrapping of two pairs each, stranded drain wire AWG26 tinned

##### 5. Sheath

PVC or LSHF, LSHF(LSOH)

#### Flame-resistance

PVC: IEC 60332-1  
LSHF(LSOH): IEC 60332-1; IEC 60754-2; IEC 61034



# UC400 Cat6 patch

Copper flexible patch cables 26 & 27AWG



Prysmian  
Group

Part Number	Type	Sheath/Colour	Pairs x cond.Øm m	Outer Ø (Mm)	Weight (kg/m)
<b>122122</b>	UC400 26 Cat6 U/UTP Patch	PVC/Grey RAL 7035	4x2x0.51L	5.6	0,0340
<b>122133</b>	UC400 26 Cat6 U/UTP Patch	LSHF/Grey RAL 7035	4x2x0.51L	5.6	0,0340
<b>122144</b>	UC400 S27 Cat6 U/FTP Patch	LSHF/Blue RAL 5012	4x2x0.42L	5.7	0,0260
<b>122155</b>	UC400 S27 Cat6 U/FTP Patch	LSHF/Blue RAL 5012	4x2x0.42L	5.7	0,0260
<b>122166</b>	UC400 S27 Cat6 U/FTP Patch	LSHF/Blue RAL 5012	4x2x0.42L	5.7	0,0260
<b>122177</b>	UC400 S27 Cat6 U/FTP Patch	LSHF/Blue RAL 5012	4x2x0.42L	5.7	0,0260
<b>122188</b>	UC400 S27 Cat6 U/FTP Patch	LSHF/Blue RAL 5012	4x2x0.42L	5.7	0,0260
<b>122199</b>	UC400 S27 Cat6 U/FTP Patch	LSHF/Blue RAL 5012	4x2x0.42L	5.7	0,0260
<b>122210</b>	UC400 S27 Cat6 U/FTP Patch	LSHF/Blue RAL 5012	4x2x0.42L	5.7	0,0260
<b>122221</b>	UC400 S27 Cat6 U/FTP Patch	LSHF/Blue RAL 5012	4x2x0.42L	5.7	0,0260
<b>122232</b>	UC400 S27 Cat6 U/FTP Patch	LSHF/Blue RAL 5012	4x2x0.42L	5.7	0,0260

