

Cable Ties Standard

Material: Polyamide 6.6 (PA66)-Halogen free

Operating Temperature: -40°C to +85°C

Flammability: UL94 V2

Application: For bundling and fixing cables, tubes, conduits. For packaging purposes and a variety of other uses.



black (BK)

Part Number	Length mm	Width mm	Bundle Ø max. mm	Min.Tensile strength (N)	Package pcs/pack
101982	75	2,2	15,0	60	100
101993	98	2,5	21,0	80	100
102004	135	2,5	32,0	80	100
102015	160	2,6	40,0	80	100
102026	200	2,6	52,0	80	100
102037	140	3,6	35,0	130	100
102048	200	3,6	50,0	130	100
102059	290	3,6	80,0	130	100
102070	370	3,6	103,0	130	100
102081	120	4,5	24,0	220	100
102092	160	4,5	40,0	220	100
102103	178	4,8	45,0	220	100
102114	200	4,8	50,0	220	100
102125	250	4,8	68,0	220	100
102136	290	4,8	79,0	220	100
102147	360	4,8	103,0	220	100
102158	390	4,8	106,0	220	100
102169	430	4,8	115,0	220	100
102180	120	7,8	25,0	540	100
102191	180	7,8	45,0	540	100
102202	210	7,8	51,0	540	100
102213	240	7,8	63,0	540	100
102224	300	7,8	80,0	540	100
102235	365	7,8	100,0	540	100
102246	450	7,8	130,0	540	100
102257	540	7,8	158,0	540	100
102268	750	7,8	220,0	540	100
102279	780	9,0	233,0	700	100
102290	225	12,5	57,0	1080	50
102301	500	12,5	143,0	1080	50
102312	720	12,5	213,0	1080	50
102323	850	12,5	255,0	1080	50
102334	1000	12,5	302,0	1080	50

Cable Ties Standard

Material: Polyamide 6.6 (PA66)-Halogen free

Operating Temperature: -40°C to +85°C

Flammability: UL94 V2

Application: For bundling and fixing cables, tubes, conduits. For packaging purposes and a variety of other uses.



natural (NA)

Part Number	Length mm	Width mm	Bundle Ø max. mm	Min.Tensile strength (N)	Package pcs/pack
102345	75	2,2	15,0	60	100
102356	98	2,5	21,0	80	100
102367	135	2,5	32,0	80	100
102378	160	2,6	40,0	80	100
102389	200	2,6	52,0	80	100
102400	140	3,6	35,0	130	100
102411	200	3,6	50,0	130	100
102422	290	3,6	80,0	130	100
102433	370	3,6	103,0	130	100
102444	120	4,5	24,0	220	100
102455	160	4,5	40,0	220	100
102466	178	4,8	45,0	220	100
102477	200	4,8	50,0	220	100
102488	250	4,8	68,0	220	100
102499	290	4,8	79,0	220	100
102510	360	4,8	103,0	220	100
102521	390	4,8	106,0	220	100
102532	430	4,8	115,0	220	100
102543	120	7,8	25,0	540	100
102554	180	7,8	45,0	540	100
102565	210	7,8	51,0	540	100
102576	240	7,8	63,0	540	100
102587	300	7,8	80,0	540	100
102598	365	7,8	100,0	540	100
102609	450	7,8	130,0	540	100
102620	540	7,8	158,0	540	100
102631	750	7,8	220,0	540	100
102642	780	9,0	233,0	700	100
102653	225	12,5	57,0	1080	50
102664	500	12,5	143,0	1080	50
102675	720	12,5	213,0	1080	50
102686	850	12,5	255,0	1080	50
102697	1000	12,5	302,0	1080	50

Cable Ties with identification plate

Material: Polyamide 6.6 (PA66)-Halogen free

Operating Temperature: -40°C to +85°C

Flammability: UL94 V2

Application: The polyamide 6.6 cable ties with marking plate, allow a quick identification through specific marking on the plate.



natural (NA)

Part Number	Length mm	Width mm	Plate Width mm	Plate Height mm	Bundle Ø max. mm	Min.Tensile strength (N)	Package pcs/pack
102708	100	2,5	25,4	8,0	20,0	80	100
102719	200	2,5	25,4	8,0	50,0	80	100
102730	110	2,5	20,4	9,1	20,0	80	100
102741	210	2,5	20,4	9,1	52,0	80	100
102752	190	4,8	13,0	28,0	48,0	220	100
102763	270	4,8	13,0	28,0	68,0	220	100