

Cable Ties MBT series ,uncoated

Material: Stainless Steel SS316 type

Operating Temperature: -80°C to +538°C

Flammability: non burning

Application: Suitable for use in the most arduous conditions or where additional security, strength, fire resistance and chemical resistance properties. Used in all industries - from mass transit, ship building, oil rigs, mining, chemical industries and many more.



Part Number	Type	Length mm	Width mm	Bundle Ø max. mm	Min.Tensile strength (N)	Package pcs/pack
102774	MBT5S	127	4,6	25,0	670,0	100
102785	MBT8S	201	4,6	50,0	670,0	100
102796	MBT14S	362	4,6	102,0	670,0	100
102807	MBT20S	521	4,6	152,0	670,0	100
102818	MBT27S	681	4,6	203,0	670,0	100
102829	MBT33S	838	4,6	254,0	670,0	100
102840	MBT8H	201	7,9	50,0	1115,0	50
102851	MBT14H	362	7,9	102,0	1115,0	50
102862	MBT20H	521	7,9	152,0	1115,0	50
102873	MBT27H	681	7,9	203,0	1115,0	50
102884	MBT33H	838	7,9	254,0	1115,0	50
102895	MBT14XH	362	12,3	102,0	2225,0	50
102906	MBT20XH	521	12,3	152,0	2225,0	50
102917	MBT27XH	681	12,3	203,0	2225,0	50
102928	MBT33XH	838	12,3	254,0	2225,0	50

Cable Ties stainless steel,uncoated
Material: Stainless Steel 304,316

Operating Temperature: -80°C to +538°C

Application: Used at ships-boats,food & medicine industries,hospitals & quarries.

Part Number	Length mm	Width mm	Strength (kg)	Package (pcs/pack)
102939	130	4,6	44,0	100
102950	200	4,6	44,0	100
102961	270	4,6	44,0	100
102972	360	4,6	44,0	100
102983	520	4,6	44,0	100
102994	680	4,6	44,0	100
103005	840	4,6	44,0	100
103016	200	7,9	111,0	100
103027	270	7,9	111,0	100
103038	360	7,9	111,0	100
103049	520	7,9	111,0	100
103060	680	7,9	111,0	100

