

Cable Glands SKINTOP® MS with Pg connection thread
Material: Brass, nickel-plated (body),polyamide (insert)

Protection rating: IP 68, 5 bar

Sealing ring: CR/NBR

Temperature range: -30 °C to +100 °C


Part Number	Thread Ø mm	SW mm	Overall length mm	Thread length mm	For Cable Ømm		Package pcs/pack
					min.	max.	
101201	MS 7	14	25	5	2,0	6,5	100
101212	MS 9	17	29	6	4,0	8,0	100
101223	MS 11	20	32	6	4,0	10,0	50
101234	MS 13,5	22	34	7	5,0	12,0	50
101245	MS 16	24	35	7	8,0	14,0	50
101256	MS 21	30	40	7	11,0	18,0	25
101267	MS 29	40	48	8	16,0	25,0	25
101278	MS 36	50	62	15	19,0	32,0	10
101289	MS 42	57	62	15	28,0	38,0	5
101300	MS 48	64	62	15	34,0	44,0	5

Cable Glands SKINTOP® MS-M metric,Versatile brass
Material: Brass, nickel-plated (body),polyamide (insert)

Protection rating: IP 68, 5 bar

Sealing ring: CR/NBR

Temperature range: -30 °C to +100 °C


Part Number	Thread Ø mm	SW mm	Overall length mm	Thread length mm	For Cable Ømm		Package pcs/pack
					min.	max.	
101311	M12 x 1,5	16	26,5	6,5	3,0	7,0	100
101322	M16 x 1,5	20	32,0	7,0	4,5	10,0	100
101333	M20 x 1,5	24	35,5	8,0	7,0	13,0	50
101344	M25 x 1,5	29	37,5	8,0	9,0	17,0	25
101355	M32 x 1,5	36	42,2	9,0	11,0	21,0	25
101366	M40 x 1,5	45	49,5	9,0	19,0	28,0	10
101377	M50 x 1,5	54	52,0	10,0	27,0	35,0	5
101388	M63 x 1,5	67	61,3	15,0	34,0	45,0	5
101399	M63 x 1,5*	75	65,5	15,0	44,0	55,0	5
101410	M75 x 1,5	95	105,0	15,0	58,0	68,0	1

*plus

Cable Glands SKINTOP® MS-SC EMC, Pg connection thread
Material: Brass, nickel-plated body, polyamide sealing

CR-O ring: NBR

Protection rating: IP 68

Temperature range: -30 °C to +100 °C


Part Number	Part Design. /Thread Ømm	min.Ø above braiding mm	Thread length mm	For Cable Ømm		Package pcs/pack
				min.	max.	
101421	MS-SC 9	4	6	3,0	8,0	50
101432	MS-SC 11	4	6	4,0	10,0	50
101443	MS-SC 13,5	4	7	5,0	12,0	25
101454	MS-SC 16	6	7	8,0	14,0	25
101465	MS-SC 21	8	7	11,0	17,5	25
101476	MS-SC 29	13	8	16,0	25,0	10
101487	MS-SC 36	16	15	19,0	32,0	5

Cable Glands SKINTOP® MS-M ATEX explosion-proof, with metric thread
Material: Brass, nickel-plated body, polyamide sealing

CR-O ring: NBR

Protection rating: IP 68-10 bar

Temperature range: -30 °C to +90 °C


Part Number	Part Design. /Thread Ømm	For Cable Ømm		SW mm	Overall length mm	Thread length mm	Package pcs/pack
		min.	max.				
101498	M12 x 1,5	3,0	7,0	16	26,5	6,5	100
101509	M16 x 1,5	4,5	10,0	20	33,0	7,0	100
101520	M20 x 1,5	7,0	13,0	24	37,0	8,0	50
101531	M25 x 1,5	9,0	17,0	29	38,5	8,0	25
101542	M32 x 1,5	11,0	21,0	36	45,5	9,0	25
101553	M40 x 1,5	19,0	28,0	45	48,0	9,0	10
101564	M50 x 1,5	26,0	35,0	54	55,5	10,0	5
101575	M63 x 1,5	34,0	45,0	67	67,0	15,0	5