

## Single Wall Heat Shrinkable Tubing ET100

**Material:** Polyolefin

**Continuous Operating Temperature:** -55°C to 135°C

**Shrink Temperature:** >90°C

**Shrink Ratio:** 2:1

**Length:** 1m

**Colour:** black(std),white-red-blue-yellow-clear-brown(on request)

**Description-Application:** Flame retardant,flexible and strong,suitable for general applications.It grants the maximum chemical resistance and safety in the electrical insulation.



### black-white-red-blue-yellow-clear-brown

Part Number	Internal Ø (min.) mm	Internal Ø (max.) mm	Wall Thickness Overall (NOM) mm	Package m/pack
<b>104831</b>	1,2	0,6	0,41	30
<b>104842</b>	1,6	0,8	0,43	30
<b>104853</b>	2,4	1,2	0,51	30
<b>104864</b>	3,2	1,6	0,51	30
<b>104875</b>	4,8	2,4	0,51	24
<b>104886</b>	6,4	3,2	0,64	24
<b>104897</b>	9,5	4,7	0,64	20
<b>104908</b>	12,7	6,4	0,64	16
<b>104919</b>	19,1	9,5	0,77	10
<b>104930</b>	25,4	12,7	0,89	6

### yellow/green

Part Number	Internal Ø (min.) mm	Internal Ø (max.) mm	Wall Thickness Overall (NOM) mm	Package m/pack
<b>104941</b>	2,4	1,2	0,51	30
<b>104952</b>	3,2	1,6	0,51	30
<b>104963</b>	4,8	2,4	0,51	24
<b>104974</b>	6,4	3,2	0,64	24
<b>104985</b>	9,5	4,7	0,64	20
<b>104996</b>	12,7	6,4	0,64	16
<b>105007</b>	19,1	9,5	0,77	10
<b>105018</b>	25,4	12,7	0,89	6

## MDT Medium-Duty Heat-Shrink Tubing

**Material:** Polyolefin

**Colour:** All sizes available in black. MDT-0400, -0800 and -1100 are also available in red.

**Description-Application:** 3 M™ MDT Tubing offers increased flexibility in combination with excellent abrasion, corrosion and environmental resistance properties and meets MILDTL-23053/15, Class 2. MDT Tubing installs easily and has shrink ratios to accommodate effective insulating and sealing over large transitions, splices and battery cables.



Part Number	Expanded I.D. (min. mm)	Recovered I.D. (max. mm)	Nominal Outer Wall Thickness (mm)	Length (m)	Colour	Package (pcs/pack)
<b>105029</b>	10.2	3.8	2.3	1.22	Red or Black	20
<b>105040</b>	20.3	5.6	2.5	1.22	Red or Black	20
<b>105051</b>	27.9	9.4	2.5	1.22	Red or Black	20
<b>105062</b>	33.0	10.9	2.5	1.22	Black	15
<b>105073</b>	38.1	12.7	2.5	1.22	Black	20
<b>105084</b>	43.2	15.2	2.5	1.22	Black	20
<b>105095</b>	50.8	19.1	2.5	1.22	Black	15
<b>105106</b>	76.2	25.4	3.0	1.22	Black	15
<b>105117</b>	109.2	38.1	3.8	1.22	Black	10