

HNA-switches, DIN 89270

Material: Brass/red brass

Voltage: 250V

Current intensity: 10 A

Protection class to EN 60 529: IP 56

Equipment: Cable entries M 24 x 1,5/Z14

Variations:

- .../S = Multi-circuit switch
- .../K = Four-way switch
- On-Off switch, 2-pole, 16A



Part Number	Cable entry	Switch Type	Weight (kg)
101008	♀	Change over switch, 1-pole	0,8
101019	♀	Change over switch, 1-pole	0,9
101030	♀	Change over switch, 1-pole	0,9
101041	♀	Change over switch, 1-pole	1,0
101052	♀	On-Off switch, 2-pole	0,8
101063	♀	On-Off switch, 2-pole	0,9
101074	♀	On-Off switch, 2-pole	0,9
101085	♀	On-Off switch, 2-pole	1,0

HNA-switches with control light

Material: Brass/red brass

Voltage: 250V

Current intensity: 10 A

Protection class to EN 60 529: IP 56

Equipment:

- Cable entries M 24 x 1,5/Z14
- Control light E 14, red, with glow lamp

Variations:

- .../S = Multi-circuit switch
- .../K = Four-way switch
- On-Off switch, 2-pole, 16A
- ...green = control light green



Part Number	Cable entry	Switch Type	Weight (kg)
101096	♀	Change over switch, 1-pole	1,0
101107	♀	On-Off switch, 2-pole	1,0