

Super Actinic /Colour 03

- Internally coated with a white fluorescent powder to convert the short-wave UV radiation into useful actinic radiation
- Emit radiation in the range 380 - 480 nm with a maximum at 420 nm
- Spectral energy distribution in accordance with the spectral sensitivity of a number of diazo copying papers
- For maximum beauty of marine aquaria, TL /03 "Aqua Coral" lamps can be used in combination with full-spectrum "Natural Daylight" fluorescent lamps

Application

- Diazo copying machines
- Marine aquaria
- Phototherapy (neonatal jaundice treatment)

Part Number	Type	Watt	Voltage	Current (A)	Base	Package (pcs/package)
127103	TLK40W/03	40	50	0,86	G13	25
127114	TL60W/10R	60	102	0,70	G13	25
127125	TL80W/10R	80	110	0,83	G13	25



Actinic BL (Black Light)

- Emit long-wave UV-A radiation in the 350 - 400 nm range
- UV-B/UV-A ratio less than 0.1% (UV-B: 280 - 315 nm)
- R (Reflector) lamps have a 200° internal reflector

Application

- Photopolymerisation processes
- Reprography
- Insect traps

Part Number	Type	Watt	Voltage	Current (A)	Base	Package (pcs/package)
127136	TL4W/10	4	29	0,170		250
127147	TL6W/10	6	42	0,160		250
127158	TL8W/10	8	56	0,145		250
127169	TLD15W/10SEC	15	51	0,335		25
127180	TLD15W/10	15	51	0,340		25
127191	TL20W/10SEC	20	19,3	0,370		25
127202	TL20W/10	20	57	0,370		25
127213	TL-K40W/10SEC	40	50	0,860		25
127224	TLK40W/10	40	50	0,860		25
127235	TLK40W/10R	40	50	0,860		25
127246	TL40W/10	40	101	0,430		25



TL /Colour 10 UV-A

- Emit long-wave UV-A radiation in the 350 - 400 nm range
- UV-B/UV-A ratio less than 0.1% (UV-B: 280 - 315 nm)
- R (Reflector) lamps have a 200° internal reflector

Application

- Photopolymerisation processes
- Reprography
- Insect traps

Part Number	Type	Watt	Voltage	Current (A)	Base	Package (pcs/pack)
127257	TL4W/10	4	29	0,170	G5	250
127268	TL6W/10	6	42	0,160	G5	250
127279	TL8W/10	8	56	0,145	G5	250
127290	TLD15W/10SEC	15	51	0,335	G13	25
127301	TLD15W/10	15	51	0,340	G13	25
127312	TL20W/10SEC	20	19,3	0,370	G13	25
127323	TL20W/10	20	57	0,370	G13	25
127334	TL-K40W/10SEC	40	50	0,860	G13	25
127345	TLK40W/10	40	50	0,860	G13	25
127356	TLK40W/10R	40	50	0,860	G13	25
127367	TL40W/10	40	101	0,430	G13	25
127378	TL60W/10R	60	102	0,700	G13	25
127389	TL80W/10R	80	110	0,830	G13	25



PL-L/Colour 10 UV-A

Part Number	Type	Watt	Voltage	Current (A)	Base	Package (pcs/pack)
127400	PLL18W/10/4P	18	58	0,375	2G11	25

