

**NSX100 Compact circuit-breakers with thermal-magnetic trip unit TM-D**
**Standards:** IEC 60947-2

**3P**
**4P**
**Connection pitch:** 35mm

**Downside connection:** front

**Upside connection:** front

**Control type:** toggle

**Mounting mode-support:** fixed-backplate

**Protection type:** overload (thermal)  
short-circuit (magnetic)

**Application:** distribution

**NSX100B 25kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>101006</b>	3P 3d	TM16D	105	86	161	
<b>101017</b>	3P 3d	TM25D	105	86	161	
<b>101028</b>	3P 3d	TM32D	105	86	161	
<b>101039</b>	3P 3d	TM40D	105	86	161	
<b>101050</b>	3P 3d	TM50D	105	86	161	
<b>101061</b>	3P 3d	TM63D	105	86	161	
<b>101072</b>	3P 3d	TM80D	105	86	161	
<b>101083</b>	3P 3d	TM100D	105	86	161	
<b>101094</b>	4P 4d	TM16D	140	86	161	
<b>101105</b>	4P 4d	TM25D	140	86	161	
<b>101116</b>	4P 4d	TM32D	140	86	161	
<b>101127</b>	4P 4d	TM40D	140	86	161	
<b>101138</b>	4P 4d	TM50D	140	86	161	
<b>101149</b>	4P 4d	TM63D	140	86	161	
<b>101160</b>	4P 4d	TM80D	140	86	161	
<b>101171</b>	4P 4d	TM100D	140	86	161	

**NSX100F 36kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>101182</b>	3P 3d	TM16D	105	86	161	
<b>101193</b>	3P 3d	TM25D	105	86	161	
<b>101204</b>	3P 3d	TM32D	105	86	161	
<b>101215</b>	3P 3d	TM40D	105	86	161	
<b>101226</b>	3P 3d	TM50D	105	86	161	
<b>101237</b>	3P 3d	TM63D	105	86	161	
<b>101248</b>	3P 3d	TM80D	105	86	161	
<b>101259</b>	3P 3d	TM100D	105	86	161	
<b>101270</b>	4P 4d	TM16D	140	86	161	
<b>101281</b>	4P 4d	TM25D	140	86	161	
<b>101292</b>	4P 4d	TM32D	140	86	161	
<b>101303</b>	4P 4d	TM40D	140	86	161	
<b>101314</b>	4P 4d	TM50D	140	86	161	
<b>101325</b>	4P 4d	TM63D	140	86	161	
<b>101336</b>	4P 4d	TM80D	140	86	161	
<b>101347</b>	4P 4d	TM100D	140	86	161	

**(continue to next page)**

**NSX100 Compact circuit-breakers with thermal-magnetic trip unit TM-D**  
**(continue from previous page)**

**NSX100N 50kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>101358</b>	3P 3d	TM16D	105	86	161	
<b>101369</b>	3P 3d	TM25D	105	86	161	
<b>101380</b>	3P 3d	TM32D	105	86	161	
<b>101391</b>	3P 3d	TM40D	105	86	161	
<b>101402</b>	3P 3d	TM50D	105	86	161	
<b>101413</b>	3P 3d	TM63D	105	86	161	
<b>101424</b>	3P 3d	TM80D	105	86	161	
<b>101435</b>	3P 3d	TM100D	105	86	161	
<b>101446</b>	4P 4d	TM16D	140	86	161	
<b>101457</b>	4P 4d	TM25D	140	86	161	
<b>101468</b>	4P 4d	TM32D	140	86	161	
<b>101479</b>	4P 4d	TM40D	140	86	161	
<b>101490</b>	4P 4d	TM50D	140	86	161	
<b>101501</b>	4P 4d	TM63D	140	86	161	
<b>101512</b>	4P 4d	TM80D	140	86	161	
<b>101523</b>	4P 4d	TM100D	140	86	161	

**NSX100H 70kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>101534</b>	3P 3d	TM16D	105	86	161	
<b>101545</b>	3P 3d	TM25D	105	86	161	
<b>101556</b>	3P 3d	TM32D	105	86	161	
<b>101567</b>	3P 3d	TM40D	105	86	161	
<b>101578</b>	3P 3d	TM50D	105	86	161	
<b>101589</b>	3P 3d	TM63D	105	86	161	
<b>101600</b>	3P 3d	TM80D	105	86	161	
<b>101611</b>	3P 3d	TM100D	105	86	161	
<b>101622</b>	4P 4d	TM16D	140	86	161	
<b>101633</b>	4P 4d	TM25D	140	86	161	
<b>101644</b>	4P 4d	TM32D	140	86	161	
<b>101655</b>	4P 4d	TM40D	140	86	161	
<b>101666</b>	4P 4d	TM50D	140	86	161	
<b>101677</b>	4P 4d	TM63D	140	86	161	
<b>101688</b>	4P 4d	TM80D	140	86	161	
<b>101699</b>	4P 4d	TM100D	140	86	161	

**NSX100 Compact circuit-breakers with electronic trip unit Micrologic 2.2**
**Standards:** IEC 60947-2

**Connection pitch:** 35mm

**Downside connection:** front

**Upside connection:** front

**Control type:** toggle

**Mounting mode-support:** fixed-backplate

**Protection type:** Instantaneous short-circuit protection/Overload protection (long time)/Short time short-circuit protection

**Application:** distribution

**3P**

**4P**

**NSX100B 25kA@380/415V**

Part Number	Type	Rating	Dimensions (mm)			Weight (kg)
			Width	Depth	Height	
<b>101710</b>	3P 3d	100	105	86	161	
<b>101721</b>	4P 4d	100	140	86	161	

**NSX100F 36kA@380/415V**

Part Number	Type	Rating	Dimensions (mm)			Weight (kg)
			Width	Depth	Height	
<b>101732</b>	3P 3d	100	105	86	161	
<b>101743</b>	4P 4d	100	140	86	161	

**NSX100N 50kA@380/415V**

Part Number	Type	Rating	Dimensions (mm)			Weight (kg)
			Width	Depth	Height	
<b>101754</b>	3P 3d	100	105	86	161	
<b>101765</b>	4P 4d	100	140	86	161	

**NSX100H 70kA@380/415V**

Part Number	Type	Rating	Dimensions (mm)			Weight (kg)
			Width	Depth	Height	
<b>101776</b>	3P 3d	100	105	86	161	
<b>101787</b>	4P 4d	100	140	86	161	

**NSX160 Compact circuit-breakers with thermal-magnetic trip unit TM-D**
**Standards:** IEC 60947-2

**3P**
**4P**
**Connection pitch:** 35mm

**Downside connection:** front

**Upside connection:** front

**Control type:** toggle

**Mounting mode-support:** fixed-backplate

**Protection type:** overload (thermal)  
short-circuit (magnetic)

**Application:** distribution

**NSX160E 16kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>101798</b>	3P 3d	TM16D	105	86	161	
<b>101809</b>	3P 3d	TM25D	105	86	161	
<b>101820</b>	3P 3d	TM32D	105	86	161	
<b>101831</b>	3P 3d	TM40D	105	86	161	
<b>101842</b>	3P 3d	TM50D	105	86	161	
<b>101853</b>	3P 3d	TM63D	105	86	161	
<b>101864</b>	3P 3d	TM80D	105	86	161	
<b>101875</b>	3P 3d	TM100D	105	86	161	
<b>101886</b>	3P 3d	TM125D	105	86	161	
<b>101897</b>	3P 3d	TM160D	105	86	161	
<b>101908</b>	4P 4d	TM16D	140	86	161	
<b>101919</b>	4P 4d	TM25D	140	86	161	
<b>101930</b>	4P 4d	TM32D	140	86	161	
<b>101941</b>	4P 4d	TM40D	140	86	161	
<b>101952</b>	4P 4d	TM50D	140	86	161	
<b>101963</b>	4P 4d	TM63D	140	86	161	
<b>101974</b>	4P 4d	TM80D	140	86	161	
<b>101985</b>	4P 4d	TM100D	140	86	161	
<b>101996</b>	4P 4d	TM125D	140	86	161	
<b>102007</b>	4P 4d	TM160D	140	86	161	

**NSX160B 25kA@380/415V**

<b>102018</b>	3P 3d	TM80D	105	86	161
<b>102029</b>	3P 3d	TM100D	105	86	161
<b>102040</b>	3P 3d	TM125D	105	86	161
<b>102051</b>	3P 3d	TM160D	105	86	161
<b>102062</b>	4P 4d	TM80D	140	86	161
<b>102073</b>	4P 4d	TM100D	140	86	161
<b>102084</b>	4P 4d	TM125D	140	86	161
<b>102095</b>	4P 4d	TM160D	140	86	161

**(continue to next page)**

**NSX160 Compact circuit-breakers with thermal-magnetic trip unit TM-D**  
**(continue from previous page)**

**NSX160F 36kA@380/415V**

<b>102106</b>	3P 3d	TM80D	105	86	161
<b>102117</b>	3P 3d	TM100D	105	86	161
<b>102128</b>	3P 3d	TM125D	105	86	161
<b>102139</b>	3P 3d	TM160D	105	86	161
<b>102150</b>	4P 4d	TM80D	140	86	161
<b>102161</b>	4P 4d	TM100D	140	86	161
<b>102172</b>	4P 4d	TM125D	140	86	161
<b>102183</b>	4P 4d	TM160D	140	86	161

**NSX160N 50kA@380/415V**

<b>102194</b>	3P 3d	TM80D	105	86	161
<b>102205</b>	3P 3d	TM100D	105	86	161
<b>102216</b>	3P 3d	TM125D	105	86	161
<b>102227</b>	3P 3d	TM160D	105	86	161
<b>102238</b>	4P 4d	TM80D	140	86	161
<b>102249</b>	4P 4d	TM100D	140	86	161
<b>102260</b>	4P 4d	TM125D	140	86	161
<b>102271</b>	4P 4d	TM160D	140	86	161

**NSX160H 70kA@380/415V**

<b>102282</b>	3P 3d	TM80D	105	86	161
<b>102293</b>	3P 3d	TM100D	105	86	161
<b>102304</b>	3P 3d	TM125D	105	86	161
<b>102315</b>	3P 3d	TM160D	105	86	161
<b>102326</b>	4P 4d	TM80D	140	86	161
<b>102337</b>	4P 4d	TM100D	140	86	161
<b>102348</b>	4P 4d	TM125D	140	86	161
<b>102359</b>	4P 4d	TM160D	140	86	161

**NSX160 Compact circuit-breakers with electronic trip unit Micrologic 2.2**
**Standards:** IEC 60947-2

**Connection pitch:** 35mm

**Downside connection:** front

**Upside connection:** front

**Control type:** toggle

**Mounting mode-support:** fixed-backplate

**Protection type:** Instantaneous short-circuit protection/Overload protection (long time)/Short time short-circuit protection

**Application:** distribution

**3P**
**4P**

**NSX160B 25kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>102370</b>	3P 3d	160	105	86	161	
<b>102381</b>	4P 4d	160	140	86	161	

**NSX160F 36kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>102392</b>	3P 3d	160	105	86	161	
<b>102403</b>	4P 4d	160	140	86	161	

**NSX160N 50kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>102414</b>	3P 3d	160	105	86	161	
<b>102425</b>	4P 4d	160	140	86	161	

**NSX160H 70kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>102436</b>	3P 3d	160	105	86	161	
<b>102447</b>	4P 4d	160	140	86	161	

**NSX250 Compact circuit-breakers with thermal-magnetic trip unit TM-D**
**Standards:** IEC 60947-2

**Connection pitch:** 35mm

**Downside connection:** front

**Upside connection:** front

**Control type:** toggle

**Mounting mode-support:** fixed-backplate

**Protection type:** overload (thermal)  
short-circuit (magnetic)

**Application:** distribution

**3P**
**4P**

**NSX250B 25kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>102458</b>	3P 3d	TM125D	105	86	161	
<b>102469</b>	3P 3d	TM160D	105	86	161	
<b>102480</b>	3P 3d	TM200D	105	86	161	
<b>102491</b>	3P 3d	TM250D	105	86	161	
<b>102502</b>	4P 4d	TM125D	140	86	161	
<b>102513</b>	4P 4d	TM160D	140	86	161	
<b>102524</b>	4P 4d	TM200D	140	86	161	
<b>102535</b>	4P 4d	TM250D	140	86	161	

**NSX250F 36kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>102546</b>	3P 3d	TM125D	105	86	161	
<b>102557</b>	3P 3d	TM160D	105	86	161	
<b>102568</b>	3P 3d	TM200D	105	86	161	
<b>102579</b>	3P 3d	TM250D	105	86	161	
<b>102590</b>	4P 4d	TM125D	140	86	161	
<b>102601</b>	4P 4d	TM160D	140	86	161	
<b>102612</b>	4P 4d	TM200D	140	86	161	
<b>102623</b>	4P 4d	TM250D	140	86	161	

**NSX250N 50kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>102634</b>	3P 3d	TM125D	105	86	161	
<b>102645</b>	3P 3d	TM160D	105	86	161	
<b>102656</b>	3P 3d	TM200D	105	86	161	
<b>102667</b>	3P 3d	TM250D	105	86	161	
<b>102678</b>	4P 4d	TM125D	140	86	161	
<b>102689</b>	4P 4d	TM160D	140	86	161	
<b>102700</b>	4P 4d	TM200D	140	86	161	
<b>102711</b>	4P 4d	TM250D	140	86	161	

(continue to next page)

**NSX250 Compact circuit-breakers with thermal-magnetic trip unit TM-D**  
**(continue from previous page)**

**NSX250H 70kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>102722</b>	3P 3d	TM125D	105	86	161	
<b>102733</b>	3P 3d	TM160D	105	86	161	
<b>102744</b>	3P 3d	TM200D	105	86	161	
<b>102755</b>	3P 3d	TM250D	105	86	161	
<b>102766</b>	4P 4d	TM125D	140	86	161	
<b>102777</b>	4P 4d	TM160D	140	86	161	
<b>102788</b>	4P 4d	TM200D	140	86	161	
<b>102799</b>	4P 4d	TM250D	140	86	161	



**NSX250 Compact circuit-breakers with electronic trip unit Micrologic 2.2**
**Standards:** IEC 60947-2

**3P**
**4P**
**Connection pitch:** 35mm

**Downside connection:** front

**Upside connection:** front

**Control type:** toggle

**Mounting mode-support:** fixed-backplate

**Protection type:** Instantaneous short-circuit protection/Overload protection (long time)/Short time short-circuit protection

**Application:** distribution

**NSX250B 25kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>102810</b>	3P 3d	250	105	86	161	
<b>102821</b>	4P 4d	250	140	86	161	

**NSX250F 36kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>102832</b>	3P 3d	250	105	86	161	
<b>102843</b>	4P 4d	250	140	86	161	

**NSX250N 50kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>102854</b>	3P 3d	250	105	86	161	
<b>102865</b>	4P 4d	250	140	86	161	

**NSX250H 70kA@380/415V**

Part Number	Type		Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	Height	
<b>102876</b>	3P 3d	250	105	86	161	
<b>102887</b>	4P 4d	250	140	86	161	

**NSX400 Compact circuit-breakers with electronic trip unit Micrologic 2.3**
**Standards:** IEC 60947-2

**3P**
**4P**
**Connection pitch:** 45mm

**Downside connection:** front

**Upside connection:** front

**Control type:** toggle

**Mounting mode-support:** fixed-backplate

**Protection type:** instantaneous short-circuit, overload (long time), short time short-circuit

**Application:** distribution

**NSX400F 36kA@380/415V**

Part Number	Type	Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	
<b>102898</b>	3P 3d	400	105	86	161
<b>102909</b>	4P 4d	400	140	86	161

**NSX400N 50kA@380/415V**

Part Number	Type	Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	
<b>102920</b>	3P 3d	400	105	86	161
<b>102931</b>	4P 4d	400	140	86	161

**NSX400H 70kA@380/415V**

Part Number	Type	Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	
<b>102942</b>	3P 3d	400	105	86	161
<b>102953</b>	4P 4d	400	140	86	161

**NSX630 Compact circuit-breakers with electronic trip unit Micrologic 2.3**
**Standards:** IEC 60947-2

**Connection pitch:** 45mm

**Downside connection:** front

**Upside connection:** front

**Control type:** toggle

**Mounting mode-support:** fixed-backplate

**Protection type:** instantaneous short-circuit, overload (long time), short time short-circuit

**Application:** distribution

**3P**

**4P**

**NSX630F 36kA@380/415V**

Part Number	Type	Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	
<b>102964</b>	3P 3d	630	105	86	161
<b>102975</b>	4P 4d	630	140	86	161

**NSX630N 50kA@380/415V**

Part Number	Type	Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	
<b>102986</b>	3P 3d	630	105	86	161
<b>102997</b>	4P 4d	630	140	86	161

**NSX630H 70kA@380/415V**

Part Number	Type	Dimensions (mm)			Weight (kg)
	Poles	Rating	Width	Depth	
<b>103008</b>	3P 3d	630	105	86	161
<b>103019</b>	4P 4d	630	140	86	161

**Earth-leakage modules Compact Vigi**

Part Number	Type	Poles	Description
<b>103030</b>	ME	3P	for NSX 100/160
<b>103041</b>	ME	4P	for NSX 100/160
<b>103052</b>	MH	3P	NSX 100/160 (200-440V)
<b>103063</b>	MH	4P	NSX 100/160 (200-440V)
<b>103074</b>	MH	3P	for NSX250 (200-440V)
<b>103085</b>	MH	4P	for NSX250 (200-440V)
<b>103096</b>	MH	3P	for NSX 100/160 (440-550V)
<b>103107</b>	MH	4P	for NSX 100/160 (440-550V)
<b>103118</b>	MH	3P	for NSX250 (440-550V)
<b>103129</b>	MH	4P	for NSX250 (440-550V)
<b>103140</b>	-	-	4 poles/3 poles adaptor - for NSX100..250
<b>103151</b>	MB	3P	for NSX400/630 (220-440V)
<b>103162</b>	MB	4P	for NSX400/630 (220-440V)
<b>103173</b>	MB	3P	for NSX400/630 (440-550V)
<b>103184</b>	MB	4P	for NSX400/630 (440-550V)
<b>103195</b>	-	-	4 poles/3 poles adaptor - for NSX400..630

