

Enclosures Spacial CRN single door, wall-mounting IP66

Material: steel

Type of door: plain, reversible, opening 120°

Characteristics:

- 3 mm standard double bar lock
- 2 M6×15 earth studs welded to the back
- 1 M6×15 stud on the door
- 4 M8×15 studs with built-in spacers for fixing mounting plates, adjustable plate support and modular chassis
- Embedded cable entry plate with a neoprene seal



Colour: grey RAL 7032

Part Number	External Dimensions (mm)			Cable Entry	Weight (kg)
	Height	Width	Depth		
102171	250	200	150	0	3.2
102182	300	250	150	A	4.2
102193	300	250	200	A	4.9
102204	300	300	150	B	5,0
102215	300	300	200	B	6,0
102226	300	400	200	C	6.4
102237	400	300	150	B	6,0
102248	400	300	200	B	6.8
102259	400	400	200	C	8,0
102270	400	600	250	D	10,0
102281	500	400	150	B	8.7
102292	500	400	200	C	9.8
102303	500	400	250	C	11,0
102314	500	500	250	D	12.8
102325	600	400	150	B	9.3
102336	600	400	200	C	10.8
102347	600	400	250	C	12.3
102358	600	500	150	B	11.3
102369	600	500	200	D	14.3
102380	600	500	250	D	16.2
102391	600	600	200	D	16.3
102402	600	600	250	D	18.2
102413	600	600	300	D	19.8
102424	700	500	200	D	17.3
102435	700	500	250	D	19.3
102446	800	600	200	D	21.8
102457	800	600	250	D	24.8
102468	800	600	300	D	26.3
102479	800	800	200	E	29.5
102490	800	800	300	E	32.5

(continue at next page)

Enclosures Spacial CRN single door, wall-mounting IP66

(continue from previous page)

Part Number	External Dimensions (mm)			Cable Entry	Weight (kg)
	Height	Width	Depth		
102501	1000	600	250	D	28.4
102512	1000	600	300	D	30.6
102523	1000	800	250	E	34.5
102534	1000	800	300	E	37.4
102545*	1000	1000	300	G	47,0
102556*	1000	1200	300	G	55,0
102567*	1200	800	300	G	45,0
102578*	1200	1000	300	G	56,0
102589*	1200	1000	400	G	61,0

*with 3-points lock

Enclosures Spacial S3X wall-mounting IP66

Material: stainless steel AISI 304L with brushed finish

Type of door: plain, reversible, opening 120°

Characteristics:

- Stainless steel hinges
- Reinforcement frame on the door
- Polyurethane or neoprene gasket
- Front gutterprofile
- Three-point locking for double door*
- Vertical support perforated rails to allow door mounted equipment



Part Number	External Dimensions (mm)			Number of locks	Number of doors
	Height	Width	Depth		
102600	300	300	150	1	1
102611	400	400	200	1	1
102622	600	400	200	2	1
102633	600	600	250	2	1
102644	700	500	250	2	1
102655	800	600	250	2	1
102666	800	800	300	2	1
102677	1000	800	300	2	1

Enclosures Spacial SM floor standing, monobloc IP55 with mounting plate on the exterior

Material: sheet steel protected in&out with textured painted polyester epoxy

Type of door: plain, opening 120°, with reinforcement frame 15x20mm with Ø5mm perforations every 25mm & Ø10mm every 25mm

Characteristics:

- front frame has 11×13mm perforations every 25mm for fittings of the mounting plate and other accessories
- locking mechanism outside of the sealed zone
- foamed-in polyurethane gasket adjustable plate support and modular chassis
- 4 mounting plate supports
- 5mm double bar lock
- cable entry plate in two pieces with sealing gasket

Colour: grey RAL 7032



Part Number	External Dimensions (mm)			Number of doors	Weight (kg)
	Height	Width	Depth		
102688	1400	600	300	1	
102699	1400	600	400	1	
102710	1400	800	300	1	
102721	1400	800	400	1	
102732	1400	1000	400	2	
102743	1400	1200	400	2	
102754	1600	600	300	1	
102765	1600	600	400	1	
102776	1600	800	300	1	
102787	1600	800	400	1	
102798	1600	1000	300	2	
102809	1600	1000	400	2	
102820	1600	1200	300	2	
102831	1600	1200	400	2	
102842	1800	600	300	1	
102853	1800	600	400	1	
102864	1800	600	500	1	
102875	1800	800	300	1	
102886	1800	800	400	1	
102897	1800	800	500	1	
102908	1800	800	600	1	
102919	1800	1000	400	1	
102930	1800	1000	400	2	
102941	1800	1000	500	2	
102952	1800	1200	400	2	
102963	1800	1200	500	2	
102974	1800	1600	400	2	
102985	1800	1600	500	2	

(continue at next page)

**Enclosures CMO PM floor standing, monobloc
IP55 with mounting plate on the exterior**

(continue from previous page)

Part Number	External Dimensions (mm)			Number of doors	Weight (kg)
	Height	Width	Depth		
102996	2000	600	300	1	
103007	2000	600	400	1	
103018	2000	600	500	1	
103029	2000	800	300	1	
103040	2000	800	400	1	
103051	2000	800	500	1	
103062	2000	800	600	1	
103073	2000	1000	400	2	
103084	2000	1000	500	2	
103095	2000	1200	400	2	
103106	2000	1200	500	2	
103117	2000	1200	600	2	
103128	2000	1600	400	2	
103139	2000	1600	500	2	
103150	2000	1600	600	2	

Boxes, metallised, painted grey
Material: die-cast aluminium

Installation temperature: Max +60°, Min -25°

Standards: EN 60529


Part Number	Internal Dimension LxHxD (mm)	IP	Package (pcs/pack)
103161	91x91x54	IP66	40
103172	128x103x57	IP66	32
103183	155x130x58	IP66	24
103194	178x156x75	IP66	16
103205	239x202x85	IP66	8
103216	294x244x114	IP66	4
103227	392x298x144	IP55	1