

CT modular contactors

CT contactors equipped with one or more normally open (NO) or normally closed (NC) contacts are controlled by latched type electrical orders. On the front face a red indicator light indicates voltage presence at the coil terminals (A1-A2). Manually operated contactors have a 4-position selector switch on their front face:

- automatic operating mode
- temporary «ON» override
- permanent «ON» override: used to lock the contactor in the ON position during installation maintenance
- shutdown

Part Number	Type	Contacts	Nominal Current (A)	Voltage (V AC)	Width in 9mm modules
114019	1P	1NC	16	12	2
114030	1P	1NC	16	24	2
114041	1P	1NC	16	230...240	2
114052	1P	1NO	25	230...240	2
114063	2P	2NC	16	12	2
114074	2P	2NC	16	24	2
114085	2P	1NO+1NC	16	230...240	2
114096	2P	1NO+1NC	16	12	2
114107	2P	1NO+1NC	16	24	2
114118	2P	2NO	16	230...240	2
114129	2P	2NO	25	230...240	2
114140	2P	2NO	25	24	2
114151	2P	2NC	25	230...240	2
114162	2P	2NO	40	230...240	4
114173	2P	2NO	63	230...240	4
114184	2P	2NO	63	24	4
114195	2P	2NO	100	230...240	6
114206	3P	3NC	16	12	4
114217	3P	3NC	16	24	4
114228	3P	3NC	16	230...240	4
114239	3P	3NO	25	230...240	4
114250	3P	3NO	40	230...240	6
114261	3P	2NO+1NC	63	230...240	6
114272	3P	3NO	63	230...240	6
114283	4P	4NC	16	12	4
114294	4P	4NC	16	24	4
114305	4P	4NO	16	230...240	4
114316	4P	2NO+2NC	16	12	4
114327	4P	2NO+2NC	16	24	4
114338	4P	2NO+2NC	16	230...240	4
114349	4P	4NO	25	230...240	4
114360	4P	4NO	25	24	4
114371	4P	4NC	25	230...240	4
114382	4P	4NC	25	24	4
114393	4P	2NO+2NC	25	230...240	4
114404	4P	4NO	40	230...240	6
114415	4P	4NC	40	230...240	6
114426	4P	4NO	63	230...240	6
114437	4P	4NO	63	24	6
114448	4P	4NC	63	230...240	6
114459	4P	4NC	63	24	6
114470	4P	2NO+2NC	63	230...240	6
114481	4P	4NO	100	230...240	12

