


Terminal Blocks - Polyethylene,clear


Insulation material: Polyethylene
Operating temperature range: -40°C to 65°C
Electricity resistance: 250-450V



Part Number	Rated Current (A)	Cross-section (mm ²)	Dimensions (mm)							Screw size	Pack. (pcs/pack)
			L	W	H1	H2	Ø	E1	E2		
127713	3	1,5/2,5/4	92,3	16,8	12,3	7,7	3,0	7,8	5,7	M2.5X4	100
127724	6	6,0	115,4	18,8	15,4	8,7	3,2	9,6	6,3	M3.0X5	100
127735	10	6,0	129,3	20,7	16,0	9,5	4,2	11,0	7,6	M3.0X6	100
127746	15	10,0	137,8	22,5	18,6	10,3	4,5	11,7	8,6	M3.0X7	100
127757	60	16,0	186,0	29,2	25,3	14,8	6,6	15,7	10,8	M4.0X9	100

Terminal Blocks - Polyamide,white

Insulation material: Polyamide 66,94V-2 grade
Operating temperature range: -30°C to 110°C
Electricity resistance: 250-450V



Part Number	Rated Current (A)	Cross-section (mm ²)	Dimensions (mm)							Screw size	Pack. (pcs/pack)
			L	W	H1	H2	Ø	E1	E2		
127768	3	1,5/2,5/4	92,3	16,8	12,3	7,7	3,0	7,8	5,7	M2.5X4	100
127779	6	6,0	115,4	18,8	15,4	8,7	3,2	9,6	6,3	M3.0X5	100
127790	10	6,0	129,3	20,7	16,0	9,5	4,2	11,0	7,6	M3.0X6	100
127801	15	10,0	137,8	22,5	18,6	10,3	4,5	11,7	8,6	M3.0X7	100
127812	60	16,0	186,0	29,2	25,3	14,8	6,6	15,7	10,8	M4.0X9	100
127823	80	25,0	226,8	36,1	29,1	18,0	7,8	19,2	13,2	M5.0X11	100
127834	100	35,0	254,6	45,0	34,7	22,3	9,0	20,5	19,2	M6.0X12	100

Terminal Blocks - Porcelain


Part Number	Cross-section (mm ²)	Strength (A)	Description	Pack. (pcs/pack)
127845	6	10,0	1-pole	
127856	6	10,0	2-pole	
127867	6	10,0	3-pole	