

## LRD 3-pole thermal overload relays

Balanced, status calibration, class 10-Manual or automatic reload

Part Number	For use with contactor	3-phase motors	
		standard power ratings	50/60Hz in AC3 (kW)
112721	LC1D09...D38		0,1-0,16
112732	LC1D09...D38		0,16-0,25
112743	LC1D09...D38		0,25-0,40
112754	LC1D09...D38		0,40-0,63
112765	LC1D09...D38		0,63-1
112776	LC1D09...D38		1-1,6
112787	LC1D09...D38		1,6-2,5
112798	LC1D09...D38		2,5-4
112809	LC1D09...D38		4-6
112820	LC1D09...D38		5,5-8
112831	LC1D09...D38		7-10
112842	LC1D12...D38		9-13
112853	LC1D18...D38		12-18
112864	LC1D25...D38		16-24
112875	LC1D32 & LC1D38		23-32
112886	LC1D40...D95		30-38
112897	LC1D40...D65		9-13
112908	LC1D40...D65		12-18
112919	LC1D40...D65		17-25
112930	LC1D40...D65		23-32
112941	LC1D40...D65		30-40
112952	LC1D40...D65		37-50
112963	LC1D40 & D65		48-65
112974	LC1D80...LC1D95		55-70
112985	LC1D80&LC1D95		63-80
112996	LC1D80&LC1D95		80-104
113007	LC1D115&LC1D150		80-104
113018	LC1D115&LC1D150		95-120
113029	LC1D150		110-140



## LR9-F thermal overload relays 30-630A

Balanced, class 10-Manual reload

Part Number	For direct mounting beneath contactor	Current setting Range (A)
113040	LC1F185	30-50
113051	LC1F185	48-80
113062	LC1F185	60-100
113073	LC1F185	90-150
113084	LC1F225 & LC1F265	132-220
113095	LC1F225-LC1F500	200-330
113106	LC1F225-LC1F500	300-500
113117	LC1F400-LC1F800	380-630

